

Mingyin Bluetooth Audio DC Style
鸣音蓝牙音响直流款



名称(Name): CY-DC model



产品参数

Product parameters



● 黑色/Black ● 白色/White

Capacity 容量: 12.8V/15AH(192WH/60000mAh) or 12.8V/30AH(384WH/120000mAh)

Input 输入: DC1、DC2、点烟器输入 14.6V/5A 充电器输入
DC1, DC2, charger input 14.6V/10A charger input
支持光伏PWM跟踪, 光伏最高输入电压24V, DC5521与点烟器
Supports photovoltaic PWM tracking, with a maximum photovoltaic input voltage of 24V and DC5521
共用不能同时插入不同电源、使用设备
and cigarette lighter Sharing cannot simultaneously plug in different power sources or use devices

Output 输出: 1. TYPE-C输出: QC3.0 MAX 12V/1.5A(18W) PD MAX 12V/1.5A(18W)
TYPE-C Output: QC3.0 MAX 12V/1.5A(18W) PD MAX 12V/1.5A(18W)
2. USB-A1输出: QC3.0 MAX 12V/1.5A(18W)
USB-A1 Output: QC3.0 MAX 12V/1.5A(18W)
3. USB-A2 USB-A3输出: 共输出MAX 5V/3A(15W)
USB-A2 USB-A3 Output: Co output MAX 5V/3A(15W)
4. DC1、DC2:12V/10A(120W) MAX
DC1、DC2:12V/10A(120W) MAX

Cell 电芯: 磷酸铁锂动力电芯33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size 尺寸: 214*125*215mm

Material 材质: PC+V0阻燃 / PC+V0 flame retardant

Color 颜色: 黑、白色(可定制颜色) / Black and white (Customizable colors)

Product weight 净重2.53kg, 毛重2.97kg
产品重量: 如有定制与实物为准/if there is customization and actual product, it shall prevail

Packaging size 包装尺寸: 260*165*260mm



名称(Name): CY-HY-300W

产品参数

Product parameters



● 黑色/Black ● 白色/White

Capacity
容量: 12.8V/15AH(192WH/60000mAh) or 12.8V/30Ah(384WH/120000mAh)

Input
输入: DC1、DC2、14.6V/5A 适配器
DC1, DC2, 14.6V/10A charger input

支持光伏PWM跟踪, 光伏最高输入电压24V, 两个DC5521电路
Supports photovoltaic PWM tracking, with a maximum photovoltaic input voltage of 24V, Two DC5521 circuits
共用不能同时插入不同电源、使用设备
shared cannot be plugged into different power sources or used with equipment at the same time

Output
输出: 1. AC1、AC2:220V or 110V 300W 50Hz/60Hz
AC1、AC2:220Vor110V 300W 50Hz/60Hz
2. TYPE-C输出: QC3.0 MAX 12V/1.5A(18W) PD MAX 12V/1.5A(18W)
TYPE-C Output: QC3.0 MAX 12V/1.5A(18W) PD MAX 12V/1.5A(18W)
3. USB-A1输出: QC3.0 MAX 12V/1.5A(18W)
USB-A1 Output: QC3.0 MAX 12V/1.5A(18W)
4. USB-A2 USB-A3输出: 共输出MAX 5V/3A(15W)
USB-A2 USB-A3 Output: Co output MAX 5V/3A(15W)
5. DC1、DC2:12V/10A(120W) MAX
DC1、DC2:12V/10A(120W) MAX

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 278*129*215mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑、白色(可定制颜色) / Black and white (Customizable colors)

Product weight
产品重量: 约2.8kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 320*170*270mm





名称(Name): CY-300W-02



产品参数

Product parameters



● 黑色/Black ● 白色/White

Capacity
容量: 12.8V/15AH(192WH/60000mAh) or 12.8V/30AH(384WH/120000mAh)

Input
输入: Xt60 充电器/Charger 14.6V/5A 70W
Xt160 光伏输入 / Xt60 Photovoltaic input

Output
输出:

1. AC交流输出(2个)共300W, 220V或者110V两个版本, 50Hz/60Hz, 纯正弦波
AC output (2) with a total of 300W, available in 220V or 110V versions, 50Hz/60Hz, pure sine wave
2. USB输出(X4个), QC3.0 MAX18W 12V/1.5A
USB outputs (X4), QC3.0 MAX18W 12V/1.5A
3. TYPE-C输出(X2个), PD/QC3.0 MAX18W 12C/1.5A
TYPE-C output (X2 pieces), PD/QC3.0 MAX18W 12C/1.5A
4. DC输出(X4个), 12V/10A MAX120W
DC output (X4 pieces), 12V/10A MAX120W
5. 照明LED灯3W高亮, 带2级调光与SOS闪亮
Lighting LED light with 3W high brightness, equipped with 2-level dimming and SOS flashing

Cell
电芯: 磷酸铁锂动力电池33140/15AH 3.2V 圆柱形
Lithium iron phosphate power cell 33140/15AH 3.2V cylindrical shape

Size
尺寸: 192*193*195mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑、白色(可定制颜色) / Black and white (Customizable colors)

Product weight
产品重量: 约2.7kg, 如有定制与实物为准 / If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 265*265*280mm



名称(Name): CY-600W-02



产品参数

Product parameters



● 黑色/Black ● 白色/White

Capacity
容量: 19.2V/30Ah(576WH/18000mAh)

Input
输入: 1. XT60 充电器/Charger 21.9V/MAX20A
2. XT60 光伏输入/Photovoltaic input 22~36V/20A MAX

Output
输出: 1. AC交流输出(3个)共600W,220V或者110V两个版本,50Hz/60Hz,正弦波
AC output (3 units) totaling 600W, available in 220V or 110V versions, 50Hz/60Hz, sine wave
2. USB输出(X4个), QC3.0 MAX18W 12V/1.5A
USB outputs (X4), QC3.0 MAX18W 12V/1.5A
3. TYPE-C输出(X2个), PD/QC3.0 MAX18W 12C/1.5A
TYPE-C outputs (X2), PD/QC3.0 MAX18W 12C/1.5A
4. DC输出 (X4个), 12V/10A MAX
DC output (X4 pieces), 12V/10A MAX
5. 照明LED灯4W高亮, 带2级调光与SOS闪亮
Lighting LED light 4W high brightness, with 2-level dimming and SOS flashing
6. 无线充15W
Wireless charging 15W

Cell
电芯: 磷酸铁锂动力电芯33140/15AH 3.2V 圆柱形
Lithium iron phosphate power cell 33140/15AH 3.2V cylindrical shape

Size
尺寸: 242*194*194mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑色/白色 (可定制颜色) Black/White (customizable color)

Product weight
产品重量: 约5.7kg, 如有定制与实物为准/if there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 33.5*28.5*28cm



名称(Name): CY-1200W-02



产品参数

Product parameters



● 黑色/Black ● 白色/White

Capacity
容量: 19.2V/60Ah(1152WH/360000mAh)

Input
输入: 1. XT60 充电器/Charger 21.9V/MAX20A
2. XT60 光伏输入/Photovoltaic input 22~36V/20A MAX

Output
输出: 1. AC交流输出(3个)共1200W,220V或者110V两个版本,50Hz/60Hz,正弦波
AC output (3 units) totaling 1200W, available in 220V or 110V versions, 50Hz/60Hz, sine wave
2. USB输出(X4个), QC3.0 MAX18W 12V/1.5A
USB outputs (X4), QC3.0 MAX18W 12V/1.5A
3. TYPE-C输出(X2个), PD/QC3.0 MAX18W 12C/1.5A
TYPE-C outputs (X2), PD/QC3.0 MAX18W 12C/1.5A
4. DC输出 (X4个), 12V/10A MAX
DC output (X4 pieces), 12V/10A MAX
5. 照明LED灯4W高亮, 带2级调光与SOS闪亮
Lighting LED light 4W high brightness, with 2-level dimming and SOS flashing
6. 无线充15W
Wireless charging 15W

Cell
电芯: 磷酸铁锂动力电芯33140/15AH 3.2V 圆柱形
Lithium iron phosphate power cell 33140/15AH 3.2V cylindrical shape

Size
尺寸: 242*194*263mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑色/白色 (可定制颜色) Black/White (customizable color)

Product weight
产品重量: 约9.8kg, 如有定制与实物为准/if there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 33.5*28.5*40.5cm



名称(Name): CY-HY-600W 型号(Model): A1-1



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/30Ah(576WH/180000mAh)

Input
输入:
1. DC5521 12V-24V/1-5A 电源适配器/AC adapter
2. DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
3. DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出:
1. AC交流 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC 点烟器+DC接头(x2个接口) 12V-10A/120W 总功率
DC Cigarette Lighter+DC connector (x2 interfaces) 12V-10A/120W total power
3. USB-A (x2个U口) QC3.0 快充 5V-3A,9V-2A,12V-1.5A /18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充5V/3A、9V/2A、2V/1.5A、12V/2.5A 30W MAX
USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
5. TYPE-PD PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
TYPE-PD PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
6. 照明LED灯 2W 高亮,带2级调光与SOS闪亮
Lighting LED light with 2W high brightness, with 2-level dimming and SOS flashing
7. 无线充/Wireless charging : 15W

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 270*210*210mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 绿色主体白色面板(可定制颜色) Green main body and white panel (Customizable colors)

Product weight 净重约6.5kg, 毛重约7.85kg
产品重量: 如有定制与实物为准/if there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-HY-600W 型号(Model): A1-2



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/30Ah(576WH/180000mAh)

Input
输入: 1. DC5521 12V-24V/1-5A 电源适配器/AC adapter
2. DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
3. DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出: 1. AC交流 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC 车充+DC接头(x2个接口) 12V-10A/120W 总功率
DC car charging+DC connector (x2 interfaces) 12V-10A/120W total power
3. USB-A (x2个U口) QC3.0 快充 5V-3A,9V-2A,12V-1.5A /18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充5V/3A、9V/2A、2V/1.5A、12V/2.5A 30W MAX
USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
5. USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7. 无线充/Wireless charging : 15W

Cell
电芯: 磷酸铁锂动力电芯33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 270*210*210mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 橙色主体白色面板(可定制颜色) Orange main body and white panel (Customizable colors)

Product weight
产品重量: 约6.5kg, 如有定制与实物为准 /if there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-HY-600W 型号(Model): A1-3



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/30Ah(576WH/180000mAh)

Input
输入:
1. DC5521 12V-24V/1-5A 电源适配器/AC adapter
2. DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
3. DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出:
1. AC交流 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC 车充+DC接头(x2个接口) 12V-10A/120W 总功率
DC car charging+DC connector (x2 interfaces) 12V-10A/120W total power
3. USB-A (x2个U口) QC3.0 快充 5V-3A,9V-2A,12V-1.5A /18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充5V/3A、9V/2A、2V/1.5A、12V/2.5A 30W MAX
USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
5. USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7. 无线充/Wireless charging : 15W

Cell
电芯: 磷酸铁锂动力电芯33140 圆柱型/Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 270*210*210mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑色主体白色面板(可定制颜色) Black main body and white panel (Customizable colors)

Product weight
产品重量: 约6.5kg, 如有定制与实物为准/if there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-HY-600W 型号(Model): B1-1



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/30Ah(576WH/180000mAh)

Input
输入: 1. DC5521 12V-24V/1-5A 电源适配器/AC adapter
2. DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
3. DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出: 1. AC交流 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC 车充+DC接头(x2个接口) 12V-10A/120W 总功率
DC car charging+DC connector (x2 interfaces) 12V-10A/120W total power
3. USB-A (x2个U口) QC3.0 快充 5V-3A,9V-2A,12V-1.5A /18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充5V/3A、9V/2A、2V/1.5A、12V/2.5A 30W MAX
USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
5. USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7. 无线充/Wireless charging : 15W

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 270*210*185mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 白色主体白色面板(可定制颜色) White main body and white panel (Customizable colors)

Product weight
产品重量: 约6.5kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-HY-600W 型号(Model): B1-2



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/30Ah(576WH/180000mAh)

Input
输入: 1. DC5521 12V-24V/1-5A 电源适配器/AC adapter
2. DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
3. DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出: 1. AC交流 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC 车充+DC接头(x2个接口) 12V-10A/120W 总功率
DC car charging+DC connector (x2 interfaces) 12V-10A/120W total power
3. USB-A (x2个U口) QC3.0 快充 5V-3A,9V-2A,12V-1.5A /18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A, 9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充5V/3A, 9V/2A, 2V/1.5A、12V/2.5A 30W MAX
USB-C1 PD/QC3.0 Fast Charging 5V/3A, 9V/2A, 2V/1.5A, 12V/2.5A 30W MAX
5. USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A, 9V-3A, 12V-3A, 15V-3A, 20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7. 无线充/Wireless charging : 15W

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 270*210*230mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 灰色主体白色面板(可定制颜色) Grey main body and white panel (Customizable colors)

Product weight
产品重量: 约6.5kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-600W 型号(Model): B1-1



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 12.8V/45Ah(576WH/180000mAh)

Input
输入: 1. 8字交流电输入接口100V~240V 额定功率200W
8-word AC input interface 100V~240V rated power 200W
2. 太阳能充电: DC1、DC2、车载点烟器输入 14.6V/10A充电器输入
Solar charging: DC1, DC2, car cigarette lighter input 14.6V/10A charger input
支持光伏PWM跟踪, 光伏最高输入电压24V, DC5521与点烟器
Supports photovoltaic PWM tracking, with a maximum photovoltaic input voltage of 24V, DC5521,
共用不能同时插入不同电源、使用设备
and cigarette lighter Sharing cannot simultaneously plug in different power sources or use devices

Output
输出: 1. AC*2 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC*2 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC1、DC2、点烟器输出 12V/10A(120W) MAX
DC1, DC2, cigarette lighter output 12V/10A (120W) MAX
3. TYPE-C输出 :OC3.0 MAX 12V/1.5A(18W)
TYPE-C output: OC3.0 MAX 12V/1.5A (18W)
4. USB-A1输出 QC3.0 MAX 12V/1.5A(18W)
USB-A1 output QC3.0 MAX 12V/1.5A (18W)
5. USB-A2 USB-A3输出 共输出MAX 5V/3A(15W)
USB-A2 USB-A3 outputs MAX 5V/3A (15W) in total
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing

Cell
电芯: 4串磷酸铁锂 /4 series of lithium iron phosphate

Size
尺寸: 270*210*188mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 橙色主体白色面板(可定制颜色) Orange main body and white panel (Customizable colors)

Product weight
产品重量: 约6kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-600W 型号(Model): B1-2



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 12.8V/45Ah(576WH/180000mAh)

Input
输入: 1. 8字交流电输入接口100V~240V 额定功率200W
8-word AC input interface 100V~240V rated power 200W
2. 太阳能充电: DC1、DC2、车载点烟器输入 14.6V/10A充电器输入
Solar charging: DC1, DC2, car cigarette lighter input 14.6V/10A charger input
支持光伏PWM跟踪, 光伏最高输入电压24V, DC5521与点烟器
Supports photovoltaic PWM tracking, with a maximum photovoltaic input voltage of 24V, DC5521,
共用不能同时插入不同电源、使用设备
and cigarette lighter Sharing cannot simultaneously plug in different power sources or use devices

Output
输出: 1. AC*2 220V或者110V 两个版本,600W,50Hz/60Hz, 正弦波
AC*2 220V or 110V versions, 600W, 50Hz/60Hz, sine wave
2. DC1、DC2、点烟器输出 12V/10A(120W) MAX
DC1, DC2, cigarette lighter output 12V/10A (120W) MAX
3. TYPE-C输出 :OC3.0 MAX 12V/1.5A(18W)
TYPE-C output: OC3.0 MAX 12V/1.5A (18W)
4. USB-A1输出 QC3.0 MAX 12V/1.5A(18W)
USB-A1 output QC3.0 MAX 12V/1.5A (18W)
5. USB-A2 USB-A3输出 共输出MAX 5V/3A(15W)
USB-A2 USB-A3 outputs MAX 5V/3A (15W) in total
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing

Cell
电芯: 4串磷酸铁锂 /4 series of lithium iron phosphate

Size
尺寸: 270*210*188mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 橙色主体白色面板(可定制颜色) Orange main body and white panel (Customizable colors)

Product weight
产品重量: 约6.5kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 345*285*280mm



名称(Name): CY-1200W 型号(Model): B2-1



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/60Ah(1152WH/360000mAh)

Input
输入: 1.XT60 21.9V/20A 充电器输入/Charger Input
2.DC5521 12V-24V/1-5A 电源适配器/AC adapter
3.DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
4.DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出: 1. AC交流 220V或者110V 两个版本,1200W,50Hz/60Hz, 正弦波
AC220V or 110V versions,1200W,50Hz/60Hz,sine wave
2. DC车充+DC接头(x2个接口)12V-10A/120W 总功率
DC car charging+DC connector(x2 interfaces)12V-10A/120W total power
3. USB-A(x2个U口)QC3.0 快充 5V-3A,9V-2A,12V-1.5A/18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A,9V-2A,12V-1.5A/18W total power
4. USB-C1 PD/OC3.0快充 5V-3A,9V-2A,12V-1.5A/12V-5A 30W MAX
USB-C1 PD/QC3.0 fast charging 5V-3A,9V-2A,12V-1.5A/18W total power
5. 5.USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7.无线充15W
Wireless charging 15W

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 280*245*250mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 橙色主体白色面板(可定制颜色) Orange main body and white panel (Customizable colors)

Product weight
产品重量: 约11.6kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 355*320*360mm



名称(Name): CY-HY-1500W 型号(Model): B2-1



产品参数

Product parameters



● 橙色/Orange ● 黑色/Black ● 银色/Silvery ● 白色/White ● 绿色/Green

Capacity
容量: 19.2V/60Ah(1152WH/360000mAh)

Input
输入: 1.XT60 21.9V/20A 充电器输入/Charger Input
2.DC5521 12V-24V/1-5A 电源适配器/AC adapter
3.DC5521 12V-24V/1-5A 车充12-24V/Car charging 12-24V
4.DC5521 12V-24V/1-5A 太阳能板 /Solar panels

Output
输出: 1. AC交流 220V或者110V 两个版本,1200W,50Hz/60Hz, 正弦波
AC220V or 110V versions, 1200W, 50Hz/60Hz, sine wave
2. DC车充+DC接头(x2个接口)12V-10A/120W 总功率
DC car charging+DC connector(x2 interfaces)12V-10A/120W total power
3. USB-A(x2个U口)QC3.0 快充 5V-3A,9V-2A,12V-1.5A/18W总功率
USB-A (x2 U-ports) QC3.0 fast charging 5V-3A,9V-2A, 12V-1.5A/18W total power
4. USB-C1 PD/QC3.0快充 5V-3A,9V-2A,12V-1.5A/12V-2.5A 30W MAX
USB-C1 PD/QC3.0 fast charging 5V-3A,9V-2A,12V-1.5A/12V-2.5A 30W MAX
5. 5.USB-C2 PD快充 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W总功率
USB-C2 PD fast charging 5V-3A,9V-3A,12V-3A,15V-3A,20V-3A/100W total power
6. 照明LED灯 1W 高亮,带2级调光与SOS闪亮
Lighting LED light with 1W high brightness, with 2-level dimming and SOS flashing
7.无线充15W
Wireless charging 15W

Cell
电芯: 磷酸铁锂动力电池33140 圆柱型 /Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 280*245*250mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑色主体白色面板(可定制颜色) Black main body and white panel (Customizable colors)

Product weight
产品重量: 约11.6kg, 如有定制与实物为准/If there is customization and actual product, it shall prevail

Packaging size
包装尺寸: 355*320*360mm



名称(Name): CY-2000W 型号(Model): A2-1



产品参数

Product parameters



● 黑色/Black



● 白色/White



● 灰色/Grey

Capacity
容量: 51.2V/45Ah(2304WH/720000mAh) or 51.2V/60Ah(3072WH/960000mAh)

Input
输入:

1. DC5521 10~45V/10A 支持光伏 MPPT 跟踪
DC5521 10~45V/10A Support photovoltaic MPPT tracking
2. XT60 10~45V MAX400W 支持光伏 MPPT 跟踪
XT60 10~45V MAX400W Support photovoltaic MPPT tracking
3. 品字交流电输入接口 180V~250V 额定功率 1000W
Pin Zi AC Input Interface 180~250V Rated power 1000W

Output
输出:

1. AC插座/AC Cocket AC220V±5% (x2两个接口/Two interfaces)
2. TYPE-C1 QC3.0 MAX 12V/1.5A(18W); PD MAX 12V/2.5A(30W)
3. TYPE-C2 PD/QC3.0 MAX 20V/5A(100W)
4. USB-A1 QC3.0 MAX 20V/3A(60W)
5. USB-A2 QC3.0 MAX 12V/1.5A(18W)
6. 无线充/Wireless charging 15W Max
7. DC1、DC、点烟器/Cigarette lighter 12V/10A(120W) MAX
8. LED灯 4-8W 高亮, 带二级调光与SOS闪亮
LED light 4-8W high brightness, with secondary dimming and SOS flashing

Cell
电芯: 磷酸铁锂动力电芯33140 圆柱型/Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 460*250*335mm

Material
材质: PC+V0阻燃 / PC+V0 flame retardant

Color
颜色: 黑、白、灰(支持定制) / Black, White, and Gray (Customizable)

Product weight
产品重量: 约23KG

Packaging size
包装尺寸: 565*355*430mm



名称(Name): CY-LG-2000W 型号(Model): A2-4



产品规格参数 Product specifications and parameters



● 黑色/Black

Capacity
容量: 51.2V/45Ah(2304WH/720000mAh) or 51.2V/60Ah(3072WH/960000mAh)

Input
输入:

1. DC5521 10~45V/10A 支持光伏 MPPT 跟踪
DC5521 10~45V/10A Support photovoltaic MPPT tracking
2. XT60 10~45V MAX400W 支持光伏 MPPT 跟踪
XT60 10~45V MAX400W Support photovoltaic MPPT tracking
3. 品字交流电输入接口 180V~250V 额定功率 1000W
Pin Zi AC Input Interface 180~250V Rated power 1000W

Output
输出:

1. AC插座/AC Cocket AC220V±5% (x2两个接口/Two interfaces)
2. TYPE-C1 QC3.0 MAX 12V/1.5A(18W); PD MAX 12V/2.5A(30W)
3. TYPE-C2 PD/QC3.0 MAX 20V/5A(100W)
4. USB-A1 QC3.0 MAX 20V/3A(60W)
5. USB-A2 QC3.0 MAX 12V/1.5A(18W)
6. DC1、DC、点烟器/Cigarette lighter 12V/10A(120W) MAX
7. LED灯 4-8W 高亮, 带二级调光与SOS闪亮
LED light 4-8W high brightness, with secondary dimming and SOS flashing

Cell
电芯: 磷酸铁锂动力电芯33140 圆柱型/Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 470*210*300mm

Material
材质: 板金 / Sheet Metal

Color
颜色: 黑 (支持定制) / Black (Customizable)

Product weight
产品重量: 约30.42KG

Packaging size
包装尺寸: 570*320*525mm



名称(Name): CY-LG-3000W 型号(Model): A2-4



产品规格参数 Product specifications and parameters



● 黑色/Black

Capacity
容量: 51.2V/60AH(3072WH/960000mAh)

Input
输入:

1. DC5521 10 ~ 45V/10A 支持光伏 MPPT 跟踪
DC5521 10 ~ 45V/10A Support photovoltaic MPPT tracking
2. XT60 10 ~ 45V MAX400W 支持光伏 MPPT 跟踪
XT60 10 ~ 45V MAX400W Support photovoltaic MPPT tracking
3. 品字交流电输入接口 180V ~ 250V 额定功率 1000W
Pin Zi AC Input Interface 180 ~ 250V Rated power 1000W

Output
输出:

1. AC插座/AC Cocket AC220V±5% (x2两个接口/Two interfaces)
2. TYPE-C1 QC3.0 MAX 12V/1.5A(18W); PD MAX 12V/2.5A(30W)
3. TYPE-C2 PD/QC3.0 MAX 20V/5A(100W)
4. USB-A1 QC3.0 MAX 20V/3A(60W)
5. USB-A2 QC3.0 MAX 12V/1.5A(18W)
6. DC1、DC、点烟器/Cigarette lighter 12V/10A(120W) MAX
7. LED灯 4-8W 高亮, 带二级调光与SOS闪亮
LED light 4-8W high brightness, with secondary dimming and SOS flashing

Cell
电芯: 磷酸铁锂动力电芯33140 圆柱型/Lithium iron phosphate power cell 33140 cylindrical type

Size
尺寸: 470*210*300mm

Material
材质: 板金 / Sheet Metal

Color
颜色: 黑 (支持定制) / Black (Customizable)

Product weight
产品重量: 约30.42KG

Packaging size
包装尺寸: 570*320*525mm



名称(Name): CY-5000W 型号(Model): A3-1



产品规格参数 Product specifications and parameters

电池容量参数:磷酸铁锂16S1P 102AH/51.2V(5222WH 5.2度电)
Battery capacity: Lithium Iron Phosphate 16S1P 102AH/51.2V(5222WH 5.2 kWh electricity)

逆变器参数/Inverter parameters

- 1 逆变器机型: 5KW 48V
Inverter model: 5KW 48V
- 2 额定输出功率: 5KVA/5KW
Rated output power: 5KVA/5KW
- 3 输出电压波形: 纯正弦波
Output voltage waveform: pure sine wave
- 4 输出电压调节: 230Vac \pm 5%
Output voltage regulation: 230Vac \pm 5%
- 5 输出频率: 60Hz 或 50Hz
Output frequency: 60Hz or 50Hz

公共设施充电模式/Public facility charging mode

- 1 充电电流 (UPS) @标准的输入电压: 60A
charging current (UPS) @ standard input voltage: 60A
- 2 浮动充电电压: 54Vdc Floating charging voltage: 54Vdc

太阳能充电模式/Solar charging mode

- 1 功率范围 /Power range: <5.5KW
- 2 PV充电电流 /PV charging current: 80A
- 3 效率/Efficiency: 98% 最大/maximum
- 4 PV阵列MPPT电压范围: 120-450Vdc
PV array MPPT voltage range

尺寸/Size: 385*535*335mm

材质/Material: 钣金/Sheet Metal

颜色/Color: 白、黑(可定制颜色) White and black (customizable colors)

产品重量/Product weight: 约60KG

包装尺寸/Packaging size: 660*500*600mm



名称(Name): CY-5000W 型号(Model): A3-2



产品规格参数 Product specifications and parameters

电池容量参数: 16串磷酸铁锂 51.2V 204AH/51.2V(10444WH 10度电)
Battery capacity: 16 series lithium iron phosphate 51.2V 204AH/51.2V (10444WH 10 kWh)

逆变器参数/Inverter parameters

- 1 逆变器机型: 5KW 48V
Inverter model: 5KW 48V
- 2 额定输出功率: 5KVA/5KW
Rated output power: 5KVA/5KW
- 3 输出电压波形: 纯正弦波
Output voltage waveform: pure sine wave
- 4 输出电压调节: 230Vac \pm 5%
Output voltage regulation: 230Vac \pm 5%
- 5 输出频率: 60Hz 或 50Hz
Output frequency: 60Hz or 50Hz

公共设施充电模式/Public facility charging mode

- 1 充电电流 (UPS) @标准的输入电压: 60A
charging current (UPS) @ standard input voltage: 60A
- 2 浮动充电电压: 54Vdc Floating charging voltage: 54Vdc

太阳能充电模式/Solar charging mode

- 1 功率范围 /Power range: <5.5KW
- 2 PV充电电流 /PV charging current: 80A
- 3 效率/Efficiency: 98% 最大/maximum
- 4 PV阵列MPPT电压范围: 120-450Vdc
PV array MPPT voltage range

尺寸/Size: 566*400*512mm

材质/Material: 钣金/Sheet Metal

颜色/Color: 白、黑(可定制颜色) White and black (customizable colors)

产品重量/Product weight: 约104.3kg

包装尺寸/Packaging size: 660*500*915mm



名称(Name): CY-5000W 型号(Model): A3-3



产品规格参数 Product specifications and parameters

电池容量参数:磷酸铁锂16串/51.2V 4层电池,1层4S4P,4层串联(20889.6WH 20度)
Battery capacity: Lithium iron phosphate 16 string/51.2V 4-layer battery, 1-layer 4S4P, 4-layer series (20889.6WH 20 degrees)

逆变器参数/Inverter parameters

- 1 逆变器机型: 5KW 48V
Inverter model: 5KW 48V
- 2 额定输出功率: 5KVA/5KW
Rated output power: 5KVA/5KW
- 3 输出电压波形: 纯正弦波
Output voltage waveform: pure sine wave
- 4 输出电压调节: 230Vac \pm 5%
Output voltage regulation: 230Vac \pm 5%
- 5 输出频率: 60Hz 或 50Hz
Output frequency: 60Hz or 50Hz

公共设施充电模式/Public facility charging mode

- 1 充电电流 (UPS) @标准的输入电压: 60A
charging current (UPS) @ standard input voltage: 60A
- 2 浮动充电电压: 54Vdc Floating charging voltage: 54Vdc

太阳能充电模式/Solar charging mode

- 1 功率范围 /Power range: <5.5KW
- 2 PV充电电流 /PV charging current: 80A
- 3 效率/Efficiency: 98% 最大/maximum
- 4 PV阵列MPPT电压范围: 120-450Vdc
PV array MPPT voltage range

尺寸/Size: 566*400*832mm

材质/Material: 钣金/Sheet Metal

颜色/Color: 白、黑(可定制颜色) White and black (customizable colors)

产品重量/Product weight: 约194.3kg

包装尺寸/Packaging size: 660*500*1000MM



名称(Name): CY-5000W 型号(Model): A3-5



产品规格参数 Product specifications and parameters

逆变器参数/Inverter parameters

- 1 逆变器机型: 5KW 48V
Inverter model: 5KW 48V
- 2 额定输出功率: 5KVA/5KW
Rated output power: 5KVA/5KW
- 3 输出电压波形: 纯正弦波
Output voltage waveform: pure sine wave
- 4 输出电压调节: 230Vac \pm 5%
Output voltage regulation: 230Vac \pm 5%
- 5 输出频率: 60Hz 或 50Hz
Output frequency: 60Hz or 50Hz

公共设施充电模式/Public facility charging mode

- 1 充电电流 (UPS) @标准的输入电压: 60A
charging current (UPS) @ standard input voltage: 60A
- 2 浮动充电电压: 54Vdc Floating charging voltage: 54Vdc

太阳能充电模式/Solar charging mode

- 1 功率范围 /Power range: <5.5KW
- 2 PV充电电流 /PV charging current: 80A
- 3 效率/Efficiency: 98% 最大/maximum
- 4 PV阵列MPPT电压范围: 120-450Vdc
PV array MPPT voltage range

尺寸/Size: 425x260x105mm

材质/Material: 钣金/Sheet Metal

颜色/Color: 白、黑(可定制颜色) White and black (customizable colors)

产品重量/Product weight: 8.18kg

包装尺寸/Packaging size: 472x310x155mm



名称(Name): CY-1000W-C CY-1500W-C 车载逆变器



产品规格参数 Product specifications and parameters

产品型号:	CY-1000W-C	CY-1500W-C
产品规格:	12VDC/1000W	12VDC/1500W
额定输入电压:	12V DC	12V DC
AC输出电压范围:	220V(± 10%)	220V(± 10%)
持续输出功率:	1000W	1500W
瞬间输出负载功率:	2000W (0.1~2S)	3000W (0.1~2S)
输出过载保护:	1000W (105~130%)	1500W (105~130%)
USB-A输出:	QC3.0 18W(5V/3A、9V/2A、12V/1.5A)	
TYPE-C输出:	PD18W(5V/3A、9V/2A、12V/1.5A)	
输出电压频率:	50/60Hz	
输出电压波形:	纯正正弦波	
直流电压工作范围:	11~15V DC	
输入低压报警:	10.5V DC(± 0.5V)	
输入低电压保护:	10.0V DC(± 0.5V)	
输入低电压恢复:	11.8V DC(± 0.5V)	
输入静态电流:	≤0.8 A DC	
输入高电压保护:	16V DC	
输入高电压恢复:	15.5V DC	
输入反接保护:	有	
产品尺寸:	330*230*100mm	330*230*100mm
产品净重/毛重:	2.7kg/3.68kg	2.6kg/3.58kg
装箱数量:	1pcs	1pcs
包装尺寸:	377X280X155mm	377X280X155mm



名称(Name): CY-2000W-C CY-2500W-C 车载逆变器



产品规格参数 Product specifications and parameters

产品型号:	CY-2000W-C	CY-2500W-C
产品规格:	24VDC/2000W	24VDC/2500W
额定输入电压:	24V DC	24V DC
AC输出电压范围:	115-230V(± 10%)	115-230V(± 10%)
持续输出功率:	2000W	2500W
瞬间输出负载功率:	4000W (0.1~2S)	5000W (0.1~2S)
输出过载保护:	2000W (105~130%)	2500W (105~130%)
USB-A输出:	QC3.0 18W(5V/3A、9V/2A、12V/1.5A)	
TYPE-C输出:	PD18W(5V/3A、9V/2A、12V/1.5A)	
输出电压频率:	50/60Hz	
输出电压波形:	纯正正弦波	
直流电压工作范围:	22~30V DC	
输入低压报警:	21V DC(± 1V)	
输入低电压保护:	20V DC(± 1V)	
输入低电压恢复:	24V DC(± 0.5V)	
输入静态电流:	≤0.6 A DC	
输入高电压保护:	32V DC	
输入高电压恢复:	31V DC	
输入反接保护:	有	
产品尺寸:	385*230*100mm	385*230*100mm
产品净重/毛重:	3.34/4.32kg	3.44/4.46kg
装箱数量:	1pcs	1pcs
包装尺寸:	472x31x155mm	472x31x155mm



名称(Name): CY-3000W-C CY-3500W-C 车载逆变器



产品规格参数 Product specifications and parameters

产品型号:	CY-3000W-C	CY-3500W-C
产品规格:	24VDC/3000W	24VDC/3500W
额定输入电压:	24V DC	24V DC
AC输出电压范围:	115-230V(± 10%)	115-230V(± 10%)
持续输出功率:	3000W	3500W
瞬间输出负载功率:	6000W (0.1~2S)	7000W (0.1~2S)
输出过载保护:	3000W (105~130%)	3500W (105~130%)
USB-A输出:	QC3.0 18W(5V/3A、9V/2A、12V/1.5A)	
TYPE-C输出:	PD18W(5V/3A、9V/2A、12V/1.5A)	
输出电压频率:	50/60Hz	
输出电压波形:	纯正正弦波	
直流电压工作范围:	22~30V DC	
输入低压报警:	21V DC(± 1V)	
输入低电压保护:	20V DC(± 1V)	
输入低电压恢复:	24V DC(± 0.5V)	
输入静态电流:	≤0.6 A DC	
输入高电压保护:	32V DC	
输入高电压恢复:	31V DC	
输入反接保护:	有	
产品尺寸:	405*230*100mm	405*230*100mm
产品净重/毛重:		
装箱数量:	1pcs	1pcs
包装尺寸:		